

The sports-style design of Riley SCRIPT™ will appeal to a wide selection of your workforce. SCRIPT™ sits snugly to the side of the face and the protection offered from the deep side arms means no separate side guard is needed for those requiring a prescription lens version.

## SPECIAL FEATURES

- ✓ Stylish sports style frame
- ✓ Integrated deep fit lateral protection
- ✓ Slim fit textured temples
- ✓ Soft TPE nose pads
- ✓ Supplied with a microfibre storage pouch



VERSIONS	REF.	LENS MARKING	FRAME MARKING	PROTECTION AGAINST	COATINGS
CLEAR	○ RLY00251	2C-1.2 e 1FTKN CE	e EN 166 FT CE	Impacts, UV radiations	TECTON 400 K&N Anti-scratch and Anti-fog / UV400 / Moisture repellent
GREY	● RLY00252	5-2.5 e 1FTKN CE	e EN 166 FT CE	Impacts, UV and Solar radiations	
POLARISED	○ RLY00253	5-2.5 e 1FT CE	e EN 166 FT CE	Impacts, UV and Solar radiations	

See overleaf for this product's technical specification

## GENERAL SPECIFICATION

LENS BASE	6mm
WEIGHT	29g

## PACKAGING

Individually contained in a polythene bag with a Euroslot

PER BOX	10
PER CARTON	200

## COMPONENT SPECIFICATION

COMPONENT	MATERIAL	FEATURES
LENS	Polycarbonate	Dual lens design, RX compatible
NOSE BRIDGE	Thermoplastic Elastomers (TPE)	Comfortable and flexible
TEMPLE	TR90 Thermoplastic	Textured grip
HINGE	Metal	Increased strength


## LENS MARKINGS

### LENS FILTER TYPE:

- 2C UV
- 5 Solar

### SCALE NUMBER (SHADE):

- 1.2 Clear or Amber
- 2.5 Grey

 Identity of the manufacturer

### OPTICAL CLASS:

- 1 High optical quality

### MECHANICAL STRENGTH:


- F Low energy impact, resists a 6mm, 0.86g ball at 45m/s
- T Protection against high-speed particles at extreme temperatures

### PERFORMANCE:

- K Resistance to scratches by fine particles
- N Resistance to fogging

 Certification mark

## FRAME MARKINGS

 Identity of the manufacturer

**EN 166:** guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

### MECHANICAL STRENGTH:

- F Low energy impact, resists a 6mm, 0.86 g ball at 45 m/s
- T Protection against high-speed particles at extreme temperatures

 Certification mark

## CLEANING AND STORAGE

**CLEANING:** The lenses should be cleaned regularly.

**MAINTENANCE:** Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfibre pouch or rigid case.

**STORAGE:** All products must be stored in a dry and clean environment.

## PART OF THE GLOBUS GROUP

Based on a substantial heritage of successfully protecting hands, Globus has grown to become one of the world leaders in worker safety, leading the way in technical innovation to provide a range of products that have set the standard for safety, productivity and wearer acceptance.

This focus on creating cutting edge personal protection solutions has now extended to eye and face protection with Riley; a new collection of high performance protective eyewear products engineered with innovation and ingenuity, designed for optimum comfort and styled for safe working.

Riley product approval certificates to CE standards will be provided on request. Riley is a registered trademark.

[www.riley-eyewear.com](http://www.riley-eyewear.com)

E: [info@riley-eyewear.com](mailto:info@riley-eyewear.com)

T: +44 (0)161 877 4747

F: +44(0)161 877 4746

Globus (Shetland) Ltd, 14 Central Park, Mosley Road, Manchester, M17 1NY, UNITED KINGDOM

