



306

BREATHABLE AND WATER REPELLENT FULLY-COATED DUAL LATEX GRIP

A durable fully-coated latex glove offering powerful grip. Aerated latex foam coating allows perspiration to escape whilst resisting rain and liquids from the outside. Ideal for heavy duty handling tasks and when exposed to changeable weather conditions.

FEATURES

- › Full foam latex coating coupled with an additional latex grip coating to the palm and fingertips
- › Seamless 13 gauge Nylon/polyester knitted liner
- › Water repellent
- › Breathable coating technology
- › Long lasting grip performance in wet and dry conditions
- › Aerated foam latex provides cushioning from minor impacts
- › Soft, comfortable fit
- › Anatomical hand shape design helps prevent hand fatigue



SUITABLE FOR

Typical Industries

- Agriculture
- Construction
- Landscaping
- Logistics
- Rail
- Renewables
- Utilities

Suitable Applications

- Banksmen
- Handling Construction Materials
- Handling Insulation
- Labouring
- Outdoor Wet Work
- Warehousing

CERTIFICATION

CAT II

EN 388:2016



2121X

See overleaf for explanation





306

PRODUCT INFORMATION

MATERIALS	LINER:	13 gauge nylon, polyester
	COATING:	Full foam latex with crinkle latex on the palm
COLOUR	Blue/black	
LENGTH (mm)	250 (size dependent)	
CUFF STYLE	Elasticated knit wrist	

ORDERING DETAILS

SIZE	CODE	PACKAGING
6/S	SHO3061	10 pairs per bag 120 pairs per case
7/M	SHO3062	
8/L	SHO3063	
9/XL	SHO3064	
10/XXL	SHO3065	

RECOMMENDATIONS FOR USE

- **USE:** General handling glove. Not suitable for thermal, electrical, chemical protection. Do not use near moving machines if there is a risk of entanglement
- **STORAGE:** Store in dry conditions in the original packaging and away from direct sunlight
- **CLEANING:** To clean, wipe with a damp cloth. Note: The performance characteristics of worn and laundered gloves may differ from the results shown. Inspect the gloves to ensure no damage is present
- **LIFETIME:** Service life depends on the glove application and therefore cannot be specified. It is the responsibility of user to ensure the glove is suitable for its intended use
- **WARNING:** Latex may cause allergies

CERTIFICATION LEGENDS

MECHANICAL HAZARDS EN 388:2016
PERFORMANCE LEVELS*

0-4	0-5	0-4	0-4	A-F	P
Abrasion Resistance	Circular Blade Cut Resistance	Tear Resistance	Puncture Resistance	Straight Blade Cut Resistance (EN ISO: 13997)	Impact Resistance

*If tests are not performed or are not applicable, 'X' will be placed instead of a number/letter

EUROPE

www.globusgroup.com

E: sales@globus.co.uk
T: +44 (0)161 877 4747
F: +44 (0)161 877 4746

MIDDLE EAST AND AFRICA

www.globusgroup.com/gcc

E: gcc@globusgroup.com
T: +971 4 882 9962
F: +971 4 882 9963



Globus Group, T2 Trafford Point, Twining Road, Trafford Park, Manchester, M17 1SH, UNITED KINGDOM
 Globus EMEA FZE, Jafza One, Tower A, Office 2201, Jebel Ali, PO Box 61195, Dubai, UNITED ARAB EMIRATES

©2020 Globus (Shetland) Ltd | SHO-DATA-306_0620_1