# sноша. **720**R

# 100% NITRILE FULLY COATED, LENGTH 30CM

Offering high resistance to chemicals and protection against abrasion. For demanding tasks that require manual exertion and complete control over work materials in wet handling conditions.

## FEATURES

- > Resistant to acids, oils and chemicals
- Surface provides a tactile feel and long-lasting grip and control in wet conditions
- Impermeable for working in damp or greasy environments
- > Anti-bacterial treatment (interior)
- > Designed for easy movement and continuous wear
- > Excellent abrasion resistance
- > Seamless
- > Extended protection to the forearm
- > Anatomically formed



## SUITABLE FOR

### **Typical Industries**

- Agriculture
- Chemical
- Construction
- Fishing/Marine
- Food
- Manufacturing
- Oil and Gas

## Suitable Applications

- Assembly
- Chemical Processing
- Cleaning
- Food Handling
- Handling Wet Objects
- Heavy Duty Handling
- Plant Maintenance

# CERTIFICATION

720R 9/L







See overleaf for explanation

EN 388:2016

3132X





**RECOMMENDATIONS FOR USE** 

of entanglement

direct sunlight

suitable for its intended use

USE: Chemical resistant glove. Not suitable for thermal, electrical protection. Do not use near moving machines if there is a risk

• STORAGE: Store in dry conditions in the original packaging and away from

 CLEANING: To clean, wipe with a damp cloth. Note: The performance characteristics of worn and laundered gloves may differ from the results shown. Inspect the gloves to ensure no damage is present
LIFETIME: Service life depends on the glove application and therefore cannot be specified. It is the responsibility of user to ensure the glove is




#### **PRODUCT INFORMATION**

MATERIALS	LINER:	Nylon, polyester
	COATING:	Nitrile
COLOUR	Dark blue	
LENGTH (mm)	300 (size dependent)	
CUFF STYLE	Gauntlet	

#### **ORDERING DETAILS**

SIZE	CODE	PACKAGING
7/S 8/M 9/L 10/XL 11/XXL	SHO7201 SHO7202 SHO7203 SHO7204 SHO7205	10 pairs per bag 120 pairs per case

#### **CERTIFICATION LEGENDS**



\*If tests are not performed or are not applicable, 'X' will be placed instead of a number/letter

L-

## RESISTANCE TO CHEMICAL PERMEATION - EN ISO 374:2016

RESISTANCE TO CHEMICAL				
CODE A 3 5 0	CHEMICAL Methanol Acetone Acetonitrile Dichloromethane	CODE J K L M		
: : : :	Carbon Disulfide Toluene Diethylamine Tetrahydrofurane Ethyl acetate	N O P S T		

CHEMICAL n-Heptane	TYPE OF GLOVES	BREAKTHROUGH TIME
Sodium hydroxide 40% Sulphuric acid 96% 65% Nitric acid	А	≥30 min for at least 6 chemicals
99% Acetic acid 25% Ammonium hydroxide	В	≥30 min for at least 3 chemicals
30% Hydrogen peroxide 40% Hydrofluoric acid 37% Formaldehyde	С	≥10 min for at least 1 chemical



PROTECTION AGAINST MICRO-ORGANISMS EN 374-5 VIRUS = Glove has passed ISO 16604: 2004 (method B)

#### **EUROPE**

#### www.globusgroup.com

- E: sales@globus.co.uk
- T: +44 (0)161 877 4747
- F: +44 (0)161 877 4746

#### MIDDLE EAST AND AFRICA

#### www.globusgroup.com/gcc

- E: gcc@globusgroup.com
- **T:** +971 4 882 9962
- F: +971 4 882 9963

Globus Group, T2 Trafford Point, Twining Road, Trafford Park, Manchester, M17 1SH, UNITED KINGDOM Globus EMEA FZE, Jafza One, Tower A, Office 2201, Jebel Ali, PO Box 61195, Dubai, UNITED ARAB EMIRATES



©2020 Globus (Shetland) Ltd | SHO-DATA-720R\_0620\_1