

FLOCK-LINED, NITRILE GAUNTLET WITH CHEMICAL RESISTANCE

Made from a special SHOWA nitrile compound, the SHOWA 730 is a lightweight, unsupported gauntlet that's resistant to a range of solvents, animal fats and other chemicals.

FEATURES

- > 100% nitrile
- > Flock-lined for enhanced comfort
- > A bisque finish allows secure handling in wet and dry conditions
- > Nitrile protects from oils, hydrocarbons and grease penetration
- > Embossed with the size for ease of pairing after laundering
- > Wrist well protected
- > Length: 33cm
- > Thickness: 0.38mm
- > Unlined version available: SHOWA 727
- Chlorinated









SUITABLE FOR

Typical Industries

- Agricultural
- Automotive
- Chemical
- Contract Cleaning
- Municipal Services
- Oil and Gas

Suitable Applications

- Cleaning
- Chemical Handling
- Degreasing
- Maintenance
- Refining
- Tank Filling

EN ISO 374-1:2016/Type A CAT III EN 388:2016



CERTIFICATION







See overleaf for explanation







Gauntlet

PRODUCT INFORMATION LINER: Unsupported, unlined COATING: Nitrile COLOUR Green LENGTH (mm) 330

ORDERING DETAILS										
	SIZE	CODE	PACKAGING	VEND COMPA	TIBLE OPTION PACKAGING					
	7/S 8/M 9/L 10/XL 11/XXL	BST7301 BST7302 BST7303 BST7304 BST7305	12 pairs per bag 144 pairs per case	BSTV7301 BSTV7302 BSTV7303 BSTV7304 BSTV7305	144 individually bagged pairs per case					

RECOMMENDATIONS FOR USE


- USE: Chemical resistant glove. Not suitable for thermal, electrical protection. Do not use near moving machines if there is a risk of entanglement
- STORAGE: Store in dry conditions in the original packaging and away from direct sunlight
- CLEANING: To clean, wipe with a damp cloth. Note: The performance characteristics of worn and laundered gloves may differ from the results shown. Inspect the gloves to ensure no damage is present
- LIFETIME: Service life depends on the glove application and therefore cannot be specified. It is the responsibility of user to ensure the glove is suitable for its intended use

CERTIFICATION LEGENDS



CUFF STYLE

MECHANICAL HAZARDS EN 388:2016 PERFORMANCE LEVELS*



*If tests are not performed or are not applicable, 'X' will be placed instead of a number/letter



8

PROTECTION AGAINST MICRO-ORGANISMS EN 374-5

VIRUS = Glove has passed ISO 16604: 2004 (method B)





RESISTANCE TO CHEMICAL PERMEATION - EN ISO 374:2016

ODE	CHEMICAL Methanol	CODE	CHEMICAL n-Heptane Sodium hydroxide 40% Sulphuric acid 96% 65% Nitric acid 99% Acetic acid 25% Ammonium hydroxide 30% Hydrogen peroxide 40% Hydrofluoric acid 37% Formaldehyde	TYPE OF GLOVES	BREAKTHROUGH TIME
	Acetone Acetonitrile Dichloromethane	K L M		А	≥30 min for at least 6 chemicals
	Carbon Disulfide Toluene Diethylamine	N O P		В	≥30 min for at least 3 chemicals
	Tetrahydrofurane Ethyl acetate	S T		С	≥10 min for at least 1 chemical

EUROPE

www.globusgroup.com

E: sales@globus.co.uk T: +44 (0)161 877 4747 F: +44 (0)161 877 4746

MIDDLE EAST AND AFRICA

www.globusgroup.com/gcc

E: gcc@globusgroup.com T: +971 4 882 9962 F: +971 4 882 9963



Globus Group, T2 Trafford Point, Twining Road, Trafford Park, Manchester, M17 1SH, UNITED KINGDOM Globus EMEA FZE, Jafza One, Tower A, Office 2201, Jebel Ali, PO Box 61195, Dubai, UNITED ARAB EMIRATES

©2020 Globus (Shetland) Ltd | SHO-DATA-730_0620_1