



BREATHABLE, WATERPROOF AND INSULATED PU COATED GLOVE

Provides warmth and protection from liquids in cold conditions, with the comfort of a breathable glove.

FEATURES

- › Innovative breathable and waterproof technology
- › Fixed insulated acrylic liner protects from cold ensuring warmth and comfort
- › Full double polyurethane (PU) coating prevents ingress from water and liquids
- › Breathable technology allows warm air and moisture from inside to escape to keep hands dry
- › Micro-roughened nitrile coating finish
- › Premium comfort and flexibility of PU
- › Seamless liner prevents irritation
- › Ergonomic fit



TEMRES technology allows warm air and moisture to escape whilst preventing ingress of liquids.



SUITABLE FOR

Typical Industries

- Agriculture
- Construction
- Logistics
- Maritime
- Offshore
- Transport

Suitable Applications

- Cold Storage
- Handling Frozen Food Packaging
- HGV Maintenance
- Light Assembly
- Outdoor Wet Work

CERTIFICATION



EN 388:2016



4221X

EN 511:2006



021

See overleaf for explanation



PRODUCT INFORMATION

MATERIALS	LINER:	Nylon, acrylic
	COATING:	Micro-ventilated polyurethane
COLOUR	Blue	
LENGTH (mm)	280 (size dependent)	
CUFF STYLE	Gauntlet	

RECOMMENDATIONS FOR USE

- **USE:** General handling glove. Not suitable for thermal, electrical, chemical protection. Do not use near moving machines if there is a risk of entanglement
- **STORAGE:** Store in dry conditions in the original packaging and away from direct sunlight
- **CLEANING:** To clean, wipe with a damp cloth. Note: The performance characteristics of worn and laundered gloves may differ from the results shown. Inspect the gloves to ensure no damage is present
- **LIFETIME:** Service life depends on the glove application and therefore cannot be specified. It is the responsibility of user to ensure the glove is suitable for its intended use

ORDERING DETAILS

SIZE	CODE	PACKAGING
8/M	SHO2822	10 pairs per pack 60 pairs per case
9/L	SHO2823	
10/XL	SHO2824	
11/XXL	SHO2825	

CERTIFICATION LEGENDS

MECHANICAL HAZARDS EN 388:2016
PERFORMANCE LEVELS*

0-4	0-5	0-4	0-4	A-F	P
Abrasion Resistance	Circular Blade Cut Resistance	Tear Resistance	Puncture Resistance	Straight Blade Cut Resistance (EN ISO: 13997)	Impact Resistance

*If tests are not performed or are not applicable, 'X' will be placed instead of a number/letter

COLD HAZARDS
EN 511

PERFORMANCE LEVELS

0-4	0-5	0 or 1
Convective Cold Resistance	Contact Cold Resistance	Water Permeability

EUROPE

www.globusgroup.com

E: sales@globus.co.uk
T: +44 (0)161 877 4747
F: +44 (0)161 877 4746

MIDDLE EAST AND AFRICA

www.globusgroup.com/gcc

E: gcc@globusgroup.com
T: +971 4 882 9962
F: +971 4 882 9963

