

INSULATED GLOVE WITH FLEXIBLE PVC SPONGE TOUCH COATING

Lightweight, fleece-lined glove with a flexible PVC sponge touch coating using Hydropellent Technology (HPT). The undulating pattern on the palm enhances grip in oily, wet and dry conditions.

FEATURES

- > Fully dipped
- > Soft fleece lining for comfort in cold conditions
- > Undulating contour grip pattern to the palm
- > Hydropellent Technology repels liquids
- > Good grip in wet and greasy conditions
- > Durable PVC sponge touch finish
- > Sanitised® antimicrobial finish provides extra freshness











SUITABLE FOR

Typical Industries

- Food
- Manufacturing
- Maintenance
- Municipal Services
- Oil and Gas
- Utilities

Suitable Applications

- Cold Storage
- Mechanical Handling in Cold
- Conditions
- Outdoor General Handling
- Packaging
- Warehousing and Distribution

CERTIFICATION





3131X





See overleaf for explanation







SKYTEC ARGON XTRA™

SUITABLE FOR

MATERIALS	LINER:	13 gauge nylon, fleece	
	COATING:	PVC HPT	
COLOUR	Black		
LENGTH (mm)	250 (size dependent)		
CUFF STYLE	Elasticated knit wrist		

ORDERING DETAILS

SIZE	CODE	PACKAGING
7/S 8/M 9/L 10/XL 11/XXL	SKY911 SKY912 SKY913 SKY914 SKY915	10 pairs per bag 60 pairs per case

RECOMMENDATIONS FOR USE


- USE: Cold resistant glove. Not suitable for thermal (heat), electrical or chemical protection. Do not use near moving machines if there is a risk of
- STORAGE: Store in dry conditions in the original packaging and away from
- CLEANING: To clean, wipe with a damp cloth. Note: The performance characteristics of worn and laundered gloves may differ from the results shown. Inspect the gloves to ensure no damage is present.
- LIFETIME: Service life depends on the glove application and therefore cannot be specified. It is the responsibility of user to ensure the glove is suitable for its intended use

CERTIFICATION LEGENDS



MECHANICAL HAZARDS EN 388:2016

PERFORMANCE LEVELS*



*If tests are not performed or are not applicable, 'X' will be placed instead of a number/letter



Water Permeability Contact Cold Resistance

EN 511

0-4

COLD HAZARDS

Convective Cold Resistance

PERFORMANCE LEVELS

0-5 0 or 1



FOOD CONTACT DIRECTIVE 2002 / 72 EC

EUROPE

www.globusgroup.com

E: sales@globus.co.uk +44 (0)161 877 4747 +44 (0)161 877 4746

MIDDLE EAST AND AFRICA

www.globusgroup.com/gcc

E: gcc@globusgroup.com +971 4 882 9962 F: +971 4 882 9963



Globus Group, T2 Trafford Point, Twining Road, Trafford Park, Manchester, M17 1SH, UNITED KINGDOM Globus EMEA FZE, Jafza One, Tower A, Office 2201, Jebel Ali, PO Box 61195, Dubai, UNITED ARAB EMIRATES

©2020 Globus (Shetland) Ltd | SKY-DATA-ARG-XTRA-0420_1